

View Online at <https://aerobasegroup.com/nsn/5930-01-018-1734>

Thread Class:

2b single pressure connection

Overall Length:

6.240 inches

Overall Height:

3.300 inches

Overall Width:

4.750 inches

Body Width:

2.240 inches

Distance Between Mounting Facility Centers:

4.250 inches

Pressure Switch Type:

Gage

Mounting Method:

Bracket

Features Provided:

Hermetically sealed case

Thready Qty Per Inch (tpi):

18 single pressure connection

Contact Action Stimulus:

Increase

Proof Pressure:

4500.00 pounds per square inch

Thread Size:

0.250 inches single pressure connection

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, single throw, normally closed, momentary action

Sensing Element Burst Pressure:

7500.00 pounds per square inch

Terminal Type:

Wire lead

Contact Load Current Rating:

400.0 milliamperes resistive load fourth voltage and 30.0 milliamperes inductive load fourth voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

+500.00/+3000.00 actuation point pounds per square inch and +275.00/+2775.00 deactuation point pounds per square inch

Contact Adjustment Type:

Internal deactuation point screw and internal actuation point screw

Contact Voltage Rating In Volts:

480.0 ac at sea level third voltage

Pressure Connector Type:

Double compression, threaded internal single connection

Frequency In Hertz:

50.0 third voltage and 60.0 third voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular w/bracket

Thread Series Designator:

Npt single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0