

View Online at <https://aerobasegroup.com/nsn/5930-01-018-2320>

Thread Class:

3b single pressure connection

Inside Diameter:

0.250 inches single connection

Thread Length:

0.488 inches single pressure connection

Overall Length:

2.953 inches

Overall Height:

2.641 inches

Overall Width:

2.812 inches

Body Height:

2.641 inches

Unthreaded Mounting Hole Diameter:

0.161 inches

Distance Between Mounting Facility Centers:

2.375 inches

Pressure Switch Type:

Gage

Mounting Method:

Unthreaded hole

Features Provided:

Manual reset button

Thready Qty Per Inch (tpi):

18 single pressure connection

Contact Action Stimulus:

Increase

Thread Size:

0.250 inches single pressure connection

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, single throw, normally closed, momentary action

Terminal Type:

Screw

Contact Load Current Rating:

9.2 amperes resistive load second voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

250.00 actuation point pounds per square inch and 189.00 deactuation point pounds per square inch

Contact Voltage Rating In Volts:

277.0 ac at sea level third voltage

Pressure Connector Type:

Swivel nut, flare, threaded internal single connection

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular w/bracket

Thread Series Designator:

Ptf-sae short single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0