

View Online at <https://aerobasegroup.com/nsn/5930-01-018-2325>

Thread Class:

2b single mounting facility

Overall Length:

Between 1.984 inches and 2.044 inches

Overall Height:

1.500 inches

Overall Width:

1.000 inches

First Flat Length:

0.480 inches single actuator

Flat Height:

0.216 inches single actuator and 0.219 inches single actuator

Shaft Diameter:

0.248 inches single actuator and 0.251 inches single actuator

Shaft Length:

0.780 inches single actuator

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

0.875 inches single mounting facility

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

2 single section rear

Throw Quantity:

2 single section rear

Mounting Method:

Threaded hole single mounting facility

Thready Qty Per Inch (tpi):

32 single mounting facility

Thread Size:

0.138 inches single mounting facility

Contact Voltage Rating In Volts:

240.0 ac at sea level

Shaft Flat/slot Angular Location:

22.5 degrees from contact position 1 single actuator

Mounting Facility Pattern:

Two position in-line single mounting facility

Switch Actuator Indexing Position Quantity:

2 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes single section rear

Switch Actuator Positioning Increment:

90.0 degrees single actuator

Contact Load Current Rating:

20.0 amperes resistive load ac at sea level

Style Designator:

Tap, square frame

Thread Series Designator:

Unc single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0