# NSN 5930-01-018-2325

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-018-2325

#### **Thread Class:**

2b single mounting facility

## **Overall Length:**

Between 1.984 inches and 2.044 inches

## **Overall Height:**

1.500 inches

#### **Overall Width:**

1.000 inches

#### First Flat Length:

0.480 inches single actuator

#### Flat Height:

0.216 inches single actuator and 0.219 inches single actuator

## Shaft Diameter:

0.248 inches single actuator and 0.251 inches single actuator

#### Shaft Length:

0.780 inches single actuator

## Individual Section Quantity:

1

## Longest Horizontal Distance Between Mounting Centers:

0.875 inches single mounting facility

## Switch Contact Basic Design:

Nonpile-up symmetrical

#### Pole Quantity:

2 single section rear

#### **Throw Quantity:**

2 single section rear

#### **Mounting Method:**

Threaded hole single mounting facility

## Thready Qty Per Inch (tpi):

32 single mounting facility

#### **Thread Size:**

0.138 inches single mounting facility

#### **Contact Voltage Rating In Volts:**

240.0 ac at sea level

## Shaft Flat/slot Angular Location:

22.5 degrees from contact position 1 single actuator

#### Mounting Facility Pattern:

Two position in-line single mounting facility

# Switch Actuator Indexing Position Quantity:

2 single actuator

Shaft Type:

Round, flatted single actuator

# NSN 5930-01-018-2325

Rotary Switch - Page 2 of 2



**Terminal Type:** Tab, solder lug **Contact Switching Action:** Breaks before makes single section rear Switch Actuator Positioning Increment: 90.0 degrees single actuator **Contact Load Current Rating:** 20.0 amperes resistive load ac at sea level Style Designator: Tap, square frame **Thread Series Designator:** Unc single mounting facility Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A052b0