NSN 5930-01-018-2326

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-018-2326

Hazardous Locations/environmental Protection:			
Dustproof			
Overall Length:			
5.376 inches			
Overall Height:			
2.906 inches			
Overall Width:			
2.813 inches			
Unthreaded Mounting Hole Diameter:			
0.221 inches single mounting facility			
Individual Section Quantity:			
2			
Knob Manufacturer Code:			
82121			
Knob Manufacturer Part Number:			
С			
Longest Horizontal Distance Between Mounting Centers:			
2.000 inches single mounting facility			
Shortest Horizontal Distance Between Mounting Centers:			
1.000 inches single mounting facility			
Longest Vertical Distance Between Mounting Centers:			
2.188 inches single mounting facility			
Switch Contact Basic Design:			
Nonpile-up symmetrical			
Pole Quantity:			
1 each section rear			
Throw Quantity:			
2 each section rear			
Mounting Method:			
Unthreaded hole single mounting facility			
Features Provided:			
Actuator knob			
Contact Voltage Rating In Volts:			
500.0 highest ac voltage rating at sea level			
Switch Actuator Momentary Position:			
Clockwise single actuator and counterclockwise single actuator			
Mounting Facility Pattern:			
Isosceles triangle single mounting facility			
Switch Actuator Indexing Position Quantity:			
2 single actuator			
Terminal Type:			
Tab w/screw			

NSN 5930-01-018-2326

Rotary Switch - Page 2 of 2



Contact	Switching	Action
---------	-----------	--------

Breaks before makes each section rear

Switch Actuator Positioning Increment:

45.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

5.0 amperes resistive load highest ac voltage rating at sea level

Style Designator:

Tap, circuit selector

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0