

View Online at <https://aerobasegroup.com/nsn/5930-01-018-2328>

Hazardous Locations/environmental Protection:

Explosion proof

Overall Height:

2.906 inches

Overall Width:

2.813 inches

Unthreaded Mounting Hole Diameter:

0.221 inches single mounting facility

Individual Section Quantity:

5

Longest Horizontal Distance Between Mounting Centers:

2.000 inches single mounting facility

Shortest Horizontal Distance Between Mounting Centers:

1.000 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

2.188 inches single mounting facility

Switch Contact Basic Design:

Nonpile-up symmetrical and nonpile-up nonsymmetrical

Pole Quantity:

1 3rd section front

Throw Quantity:

2 3rd section front

Contact Voltage Rating In Volts:

125.0 ac at sea level

Switch Actuator Momentary Position:

Counterclockwise single actuator

Mounting Facility Pattern:

Isosceles triangle single mounting facility

Switch Actuator Indexing Position Quantity:

3 single actuator

Terminal Type:

Screw

Contact Switching Action:

Breaks before makes 2nd section front

Contact Load Current Rating:

20.0 amperes resistive load ac at sea level

Style Designator:

Tap, circuit selector

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0