NSN 5930-01-018-2332

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-018-2332

| Overall Length: | | | | | |
|---|--|--|--|--|--|
| 9.781 inches | | | | | |
| Overall Height: | | | | | |
| 2.906 inches | | | | | |
| Overall Width: | | | | | |
| 2.812 inches | | | | | |
| Unthreaded Mounting Hole Diameter: | | | | | |
| 0.221 inches single mounting facility | | | | | |
| Individual Section Quantity: | | | | | |
| 8 | | | | | |
| Knob Manufacturer Code: | | | | | |
| 82121 | | | | | |
| Knob Manufacturer Part Number: | | | | | |
| В | | | | | |
| Knob Specificationial Markings: | | | | | |
| Off oper test | | | | | |
| Longest Horizontal Distance Between Mounting Centers: | | | | | |
| 2.000 inches single mounting facility | | | | | |
| Shortest Horizontal Distance Between Mounting Centers: | | | | | |
| 1.000 inches single mounting facility | | | | | |
| Longest Vertical Distance Between Mounting Centers: | | | | | |
| 2.188 inches single mounting facility | | | | | |
| Switch Contact Basic Design: | | | | | |
| Nonpile-up nonsymmetrical | | | | | |
| Mounting Method: | | | | | |
| Bracket single mounting facility and unthreaded hole single mounting facility | | | | | |
| Features Provided: | | | | | |
| Actuator knob | | | | | |
| Contact Voltage Rating In Volts: | | | | | |
| 500.0 highest ac voltage rating at sea level | | | | | |
| Mounting Facility Pattern: | | | | | |
| Isosceles triangle single mounting facility | | | | | |
| Switch Actuator Indexing Position Quantity: | | | | | |
| 3 single actuator | | | | | |
| Terminal Type: | | | | | |
| Tab w/screw | | | | | |
| Contact Switching Action: | | | | | |
| Makes before breaks 6th section periphery | | | | | |
| | | | | | |
| Switch Actuator Positioning Increment: | | | | | |
| Switch Actuator Positioning Increment: 45.0 degrees single actuator | | | | | |

Fixed stop single actuator

NSN 5930-01-018-2332

Rotary Switch - Page 2 of 2



| Co | ntact | I oad | Current | Rating: |
|----|--------|-------|---------|-----------|
| vu | ıııacı | Luau | Current | ivatiliu. |

5.0 amperes resistive load highest ac voltage rating at sea level

Precious Material And Location:

Contact and terminal surfaces silver

Precious Material:

Silver

Style Designator:

Tap, circuit selector

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0