NSN 5930-01-018-2334

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-018-2334

| · |
|---|
| Overall Length: |
| 6.281 inches |
| Overall Height: |
| 2.906 inches |
| Overall Width: |
| 2.812 inches |
| Unthreaded Mounting Hole Diameter: |
| 0.221 inches single mounting facility |
| Individual Section Quantity: |
| 4 |
| Knob Manufacturer Code: |
| 82121 |
| Knob Manufacturer Part Number: |
| В |
| Knob Specificationial Markings: |
| Norm abnorm emer |
| Longest Horizontal Distance Between Mounting Centers: |
| 2.000 inches single mounting facility |
| Shortest Horizontal Distance Between Mounting Centers: |
| 1.000 inches single mounting facility |
| Longest Vertical Distance Between Mounting Centers: |
| 2.188 inches single mounting facility |
| Switch Contact Basic Design: |
| Nonpile-up nonsymmetrical |
| Mounting Method: |
| Bracket single mounting facility and unthreaded hole single mounting facility |
| Features Provided: |
| Actuator knob |
| Contact Voltage Rating In Volts: |
| 500.0 highest ac voltage rating at sea level |
| Mounting Facility Pattern: |
| Isosceles triangle single mounting facility |
| Switch Actuator Indexing Position Quantity: |
| 3 single actuator |
| Terminal Type: |
| Tab w/screw |
| Contact Switching Action: |
| Breaks before makes each section front |
| Switch Actuator Positioning Increment: |
| 45.0 degrees single actuator |
| Switch Actuator Stop Device Type: |

Fixed stop single actuator

NSN 5930-01-018-2334

Rotary Switch - Page 2 of 2



Contact Load Current Rating:

5.0 amperes resistive load highest ac voltage rating at sea level

Precious Material And Location:

Contact and terminal surfaces silver

Precious Material:

Silver

Style Designator:

Tap, circuit selector

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0