

View Online at <https://aerobasegroup.com/nsn/5930-01-018-2343>

Thread Length:

0.292 inches single mounting facility and 0.332 inches single mounting facility

Hazardous Locations/environmental Protection:

Explosion proof

Overall Length:

2.183 inches

Overall Width:

Between 1.180 inches and 1.220 inches

First Flat Length:

0.230 inches single actuator and 0.270 inches single actuator

Flat Height:

0.084 inches single actuator and 0.104 inches single actuator

Shaft Diameter:

0.124 inches single actuator and 0.127 inches single actuator

Shaft Length:

0.647 inches single actuator and 0.727 inches single actuator

Nonturn Device Radius:

0.245 inches at 3: 00 o'clock and 0.275 inches at 3: 00 o'clock

Individual Section Quantity:

3

Nonturn Device Type:

Tab at 3: 00 o'clock

Operating Temperature Range:

-65.0/+85.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section front

Throw Quantity:

3 each section rear

Mounting Method:

Threaded bushing w/panel seal single mounting facility

Thread Size:

0.250 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Shaft Flat/slot Angular Location:

180.0 degrees from contact position 1 single actuator

Rotor Through Connection Quantity:

1 each section

Switch Actuator Indexing Position Quantity:

12 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Printed circuit

Contact Switching Action:

Breaks before makes each section rear

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Detent Rotational Torque Range:

+8.000/+64.000 inch-ounces single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

250.0 milliamperes resistive load dc at sea level and 20.0 milliamperes inductive load dc at sea level

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0