## NSN 5930-01-018-2727

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-018-2727

**Thread Class:** 

2a single mounting facility

Thread Length:

0.437 inches single mounting facility

**Hazardous Locations/environmental Protection:** 

Explosion proof

**Overall Length:** 

2.245 inches

First Flat Length:

0.250 inches single actuator

Flat Height:

0.216 inches single actuator

**Shaft Diameter:** 

0.250 inches single actuator

**Shaft Length:** 

0.437 inches single actuator

**Overall Diameter:** 

Between 1.000 inches and 1.306 inches

**Individual Section Quantity:** 

2

**Nonturn Device Type:** 

Slotted bushing at 3: 00 o'clock

**Switch Contact Basic Design:** 

Nonpile-up symmetrical

**Pole Quantity:** 

2 each section front

**Throw Quantity:** 

4 each section rear

**Mounting Method:** 

Threaded bushing w/panel seal single mounting facility

**Thread Size:** 

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:** 

28.0 dc at sea level

**Shaft Flat/slot Angular Location:** 

216.0 degrees from nonturn device single actuator

**Rotor Through Connection Quantity:** 

2 each section

**Switch Actuator Indexing Position Quantity:** 

4 single actuator

**Shaft Type:** 

Round, flatted single actuator

## NSN 5930-01-018-2727

Rotary Switch - Page 2 of 2

A052b0



Terminal Type:
Tab, solder lug
Contact Switching Action:
Breaks before makes each section rear
Switch Actuator Positioning Increment:
36.0 degrees single actuator
Detent Rotational Torque Range:
+1.000/+4.500 inch-pounds single actuator
Switch Actuator Stop Device Type:
Fixed stop single actuator
Contact Load Current Rating:
75.0 milliamperes resistive load ac at sea level
Style Designator:
Tap, circular, bushing mount
Test Data Document:
81349-mil-s-3786 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Unef single mounting facility
Specification Data:
81349-mil-s-3786/4 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: