## NSN 5930-01-018-5736

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-018-5736

Overall Length:
5.188 inches
Overall Height:
2.750 inches
Overall Width:
2.812 inches
Body Length:
4.625 inches
Capillary Tube Length:
120.0 inches
Bulb Length:
3.625 inches
Bulb Diameter:
0.688 inches
Longest Horizontal Distance Between Mounting Centers:
2.406 inches
Shortest Horizontal Distance Between Mounting Centers:
1.750 inches
Longest Vertical Distance Between Mounting Centers:
3.281 inches
Tempurature Sensing Element Type:
Capillary tube-bulb
Mounting Method:
Bracket
Features Provided:
Electrical access port
Contact Action Stimulus:
Increase
Mounting Facility Pattern:
Isosceles triangle
Nonpile-up Contact Arrangement:
1 two circuit, double break/double make, one position momentary
Terminal Type:
Screw
Contact Load Current Rating:
9.6 amperes resistive load third voltage
Contact Adjustability:
,
Deactuation point adjustable and actuation point adjustable

**Contact Adjustment Type:** 

External deactuation point screw and external actuation point screw

+70.00/+140.00 actuation point degrees fahrenheit and +65.00/+138.00 deactuation point degrees fahrenheit

## NSN 5930-01-018-5736

Thermostatic Switch - Page 2 of 2



Contact Voltage Rating In Volts:
550.0 dc at sea level fourth voltage
Media For Which Designed:
Gas or liquid

Gas or liquid

**Style Designator:** 

Rectangular

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A048b0