NSN 5930-01-018-5736

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-018-5736

| Overall Length: |
|---|
| 5.188 inches |
| Overall Height: |
| 2.750 inches |
| Overall Width: |
| 2.812 inches |
| Body Length: |
| 4.625 inches |
| Capillary Tube Length: |
| 120.0 inches |
| Bulb Length: |
| 3.625 inches |
| Bulb Diameter: |
| 0.688 inches |
| Longest Horizontal Distance Between Mounting Centers: |
| 2.406 inches |
| Shortest Horizontal Distance Between Mounting Centers: |
| 1.750 inches |
| Longest Vertical Distance Between Mounting Centers: |
| 3.281 inches |
| Tempurature Sensing Element Type: |
| Capillary tube-bulb |
| Mounting Method: |
| Bracket |
| Features Provided: |
| Electrical access port |
| Contact Action Stimulus: |
| Increase |
| Mounting Facility Pattern: |
| Isosceles triangle |
| Nonpile-up Contact Arrangement: |
| 1 two circuit, double break/double make, one position momentary |
| Terminal Type: |
| Screw |
| Contact Load Current Rating: |
| 9.6 amperes resistive load third voltage |
| Contact Adjustability: |
| , |
| Deactuation point adjustable and actuation point adjustable |

Contact Adjustment Type:

External deactuation point screw and external actuation point screw

+70.00/+140.00 actuation point degrees fahrenheit and +65.00/+138.00 deactuation point degrees fahrenheit

NSN 5930-01-018-5736

Thermostatic Switch - Page 2 of 2



| Contact Voltage Rating In Volts: |
|--------------------------------------|
| 550.0 dc at sea level fourth voltage |
| Media For Which Designed: |
| Gas or liquid |

Gas or liquid

Style Designator:

Rectangular

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A048b0