NSN 5930-01-018-5741

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-018-5741

view Online at https://aerobasegroup.com/hsn/5930-01-016-5741
Overall Length:
7.250 inches
Overall Height:
2.906 inches
Overall Width:
2.812 inches
Unthreaded Mounting Hole Diameter:
0.221 inches single mounting facility
Individual Section Quantity:
5
Longest Horizontal Distance Between Mounting Centers:
2.000 inches single mounting facility
Shortest Horizontal Distance Between Mounting Centers:
1.000 inches single mounting facility
Longest Vertical Distance Between Mounting Centers:
2.188 inches single mounting facility
Switch Contact Basic Design:
Nonpile-up nonsymmetrical
Mounting Method:
Bracket single mounting facility and unthreaded hole single mounting facility
Features Provided:
- Catalog I Torraga
Actuator knob
Actuator knob
Actuator knob Contact Voltage Rating In Volts:
Actuator knob Contact Voltage Rating In Volts: 600.0 ac at sea level
Actuator knob Contact Voltage Rating In Volts: 600.0 ac at sea level Mounting Facility Pattern:
Actuator knob Contact Voltage Rating In Volts: 600.0 ac at sea level Mounting Facility Pattern: Isosceles triangle single mounting facility
Actuator knob Contact Voltage Rating In Volts: 600.0 ac at sea level Mounting Facility Pattern: Isosceles triangle single mounting facility Switch Actuator Indexing Position Quantity:
Actuator knob Contact Voltage Rating In Volts: 600.0 ac at sea level Mounting Facility Pattern: Isosceles triangle single mounting facility Switch Actuator Indexing Position Quantity: 5 single actuator
Actuator knob Contact Voltage Rating In Volts: 600.0 ac at sea level Mounting Facility Pattern: Isosceles triangle single mounting facility Switch Actuator Indexing Position Quantity: 5 single actuator Terminal Type:
Actuator knob Contact Voltage Rating In Volts: 600.0 ac at sea level Mounting Facility Pattern: Isosceles triangle single mounting facility Switch Actuator Indexing Position Quantity: 5 single actuator Terminal Type: Tab w/screw
Actuator knob Contact Voltage Rating In Volts: 600.0 ac at sea level Mounting Facility Pattern: Isosceles triangle single mounting facility Switch Actuator Indexing Position Quantity: 5 single actuator Terminal Type: Tab w/screw Contact Switching Action:
Actuator knob Contact Voltage Rating In Volts: 600.0 ac at sea level Mounting Facility Pattern: Isosceles triangle single mounting facility Switch Actuator Indexing Position Quantity: 5 single actuator Terminal Type: Tab w/screw Contact Switching Action: Breaks before makes each section periphery
Actuator knob Contact Voltage Rating In Volts: 600.0 ac at sea level Mounting Facility Pattern: Isosceles triangle single mounting facility Switch Actuator Indexing Position Quantity: 5 single actuator Terminal Type: Tab w/screw Contact Switching Action: Breaks before makes each section periphery Switch Actuator Positioning Increment:
Actuator knob Contact Voltage Rating In Volts: 600.0 ac at sea level Mounting Facility Pattern: Isosceles triangle single mounting facility Switch Actuator Indexing Position Quantity: 5 single actuator Terminal Type: Tab w/screw Contact Switching Action: Breaks before makes each section periphery Switch Actuator Positioning Increment: 45.0 degrees single actuator
Actuator knob Contact Voltage Rating In Volts: 600.0 ac at sea level Mounting Facility Pattern: Isosceles triangle single mounting facility Switch Actuator Indexing Position Quantity: 5 single actuator Terminal Type: Tab w/screw Contact Switching Action: Breaks before makes each section periphery Switch Actuator Positioning Increment: 45.0 degrees single actuator Contact Load Current Rating:
Contact Voltage Rating In Volts: 600.0 ac at sea level Mounting Facility Pattern: Isosceles triangle single mounting facility Switch Actuator Indexing Position Quantity: 5 single actuator Terminal Type: Tab w/screw Contact Switching Action: Breaks before makes each section periphery Switch Actuator Positioning Increment: 45.0 degrees single actuator Contact Load Current Rating: 20.0 amperes resistive load ac at sea level
Contact Voltage Rating In Volts: 600.0 ac at sea level Mounting Facility Pattern: Isosceles triangle single mounting facility Switch Actuator Indexing Position Quantity: 5 single actuator Terminal Type: Tab w/screw Contact Switching Action: Breaks before makes each section periphery Switch Actuator Positioning Increment: 45.0 degrees single actuator Contact Load Current Rating: 20.0 amperes resistive load ac at sea level Precious Material And Location:
Actuator knob Contact Voltage Rating In Volts: 600.0 ac at sea level Mounting Facility Pattern: Isosceles triangle single mounting facility Switch Actuator Indexing Position Quantity: 5 single actuator Terminal Type: Tab w/screw Contact Switching Action: Breaks before makes each section periphery Switch Actuator Positioning Increment: 45.0 degrees single actuator Contact Load Current Rating: 20.0 amperes resistive load ac at sea level Precious Material And Location: Contact and terminal surfaces silver

Tap, circuit selector

NSN 5930-01-018-5741

Rotary Switch - Page 2 of 2



_				-		
C	h	Δ	Iŧ.		ife:	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0