## NSN 5930-01-018-5742

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-018-5742

Hazardous Locations/environmental Protection:
Dustproof
Overall Length:
7.250 inches
Overall Height:
2.906 inches
Overall Width:
2.812 inches
Unthreaded Mounting Hole Diameter:
0.221 inches single mounting facility
Individual Section Quantity:
5
Knob Manufacturer Code:
82121
Knob Manufacturer Part Number:
С
Longest Horizontal Distance Between Mounting Centers:
2.000 inches single mounting facility
Shortest Horizontal Distance Between Mounting Centers:
1.000 inches single mounting facility
Longest Vertical Distance Between Mounting Centers:
2.188 inches single mounting facility
Switch Contact Basic Design:
Nonpile-up nonsymmetrical
Mounting Method:
Bracket single mounting facility and unthreaded hole single mounting facility
Features Provided:
Actuator knob
Contact Voltage Rating In Volts:
500.0 highest ac voltage rating at sea level
Mounting Facility Pattern:
Isosceles triangle single mounting facility
Switch Actuator Indexing Position Quantity:
6 single actuator
Terminal Type:
Tab w/screw
Contact Switching Action:
Breaks before makes each section periphery
Switch Actuator Positioning Increment:
45.0 degrees single actuator
Contact Load Current Pating

Contact Load Current Rating

5.0 amperes resistive load highest ac voltage rating at sea level

## NSN 5930-01-018-5742

Rotary Switch - Page 2 of 2



Contact and terminal surfaces silver

**Precious Material:** 

Silver

Style Designator:

Tap, circuit selector

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A052b0