Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-018-5742

-	zardous Locations/environmental Protection:
	stproof
	erall Length:
	50 inches
	erall Height:
2.9	06 inches
Ov	erall Width:
2.8	12 inches
Un	threaded Mounting Hole Diameter:
0.2	21 inches single mounting facility
Ind	ividual Section Quantity:
5	
Kn	ob Manufacturer Code:
821	121
Kn	ob Manufacturer Part Number:
С	
Loi	ngest Horizontal Distance Between Mounting Centers:
2.0	00 inches single mounting facility
She	ortest Horizontal Distance Between Mounting Centers:
1.0	00 inches single mounting facility
Loi	ngest Vertical Distance Between Mounting Centers:
2.1	88 inches single mounting facility
Sw	itch Contact Basic Design:
Noi	npile-up nonsymmetrical
Мо	unting Method:
Bra	cket single mounting facility and unthreaded hole single mounting facility
Fea	atures Provided:
Act	uator knob
Со	ntact Voltage Rating In Volts:
500	0.0 highest ac voltage rating at sea level
Мо	unting Facility Pattern:
Iso	sceles triangle single mounting facility
Sw	itch Actuator Indexing Position Quantity:
6 si	ingle actuator
Ter	minal Type:
Tab	o w/screw
Со	ntact Switching Action:
Bre	eaks before makes each section periphery
Sw	itch Actuator Positioning Increment:
45.	0 degrees single actuator
	ntact Load Current Rating:

NSN 5930-01-018-5742

Rotary Switch - Page 2 of 2



Precious Material And Location:

Contact and terminal surfaces silver

Precious Material:

Silver

Style Designator:

Tap, circuit selector

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A052b0