## NSN 5930-01-018-6857

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-018-6857

Hazardous Locations/environmental Protection:
Explosion proof
Overall Length:
8.407 inches
Overall Height:
2.906 inches
Overall Width:
2.812 inches
Unthreaded Mounting Hole Diameter:
0.221 inches single mounting facility
Individual Section Quantity:
10
Knob Manufacturer Code:
82121
Knob Manufacturer Part Number:
В
Longest Horizontal Distance Between Mounting Centers:
2.000 inches single mounting facility
Shortest Horizontal Distance Between Mounting Centers:
1.000 inches single mounting facility
Longest Vertical Distance Between Mounting Centers:
2.388 inches single mounting facility
Operating Tempurature Range:
-65.0/+125.0 degrees celsius
Switch Contact Basic Design:
Nonpile-up symmetrical
Pole Quantity:
1 each section front
Throw Quantity:
9 each section front
Mounting Method:
Unthreaded hole single mounting facility
Features Provided:
Actuator knob
Contact Voltage Rating In Volts:
125.0 ac at sea level
Shaft Flat/slot Angular Location:
60.0 degrees from contact position 1 single actuator
Mounting Facility Pattern:
Isosceles triangle single mounting facility
Switch Actuator Indexing Position Quantity:

10 single actuator

## NSN 5930-01-018-6857

Rotary Switch - Page 2 of 2



Shaft Type:
Rectangular/square, threaded hole single actuator
Square Shaft Size:
0.250 inches single actuator
Terminal Type:
Tab w/screw
Contact Switching Action:
Breaks before makes each section front
Switch Actuator Positioning Increment:
30.0 degrees single actuator
Switch Actuator Stop Device Type:
Fixed stop single actuator
Contact Load Current Rating:
7.5 amperes resistive load ac at sea level
Style Designator:
Tap, circuit selector
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiia:

A052b0