

View Online at <https://aerobasegroup.com/nsn/5930-01-018-7312>

**Thread Length:**

0.360 inches single mounting facility and 0.390 inches single mounting facility

**Overall Length:**

3.828 inches

**First Flat Length:**

0.235 inches single actuator and 0.265 inches single actuator

**Flat Height:**

0.203 inches single actuator and 0.233 inches single actuator

**Shaft Diameter:**

0.247 inches single actuator and 0.250 inches single actuator

**Shaft Length:**

1.798 inches single actuator and 1.828 inches single actuator

**Overall Diameter:**

Between 0.985 inches and 1.015 inches

**Nonturn Device Radius:**

0.370 inches at 3:00 o'clock and 0.380 inches at 3:00 o'clock

**Individual Section Quantity:**

1

**Nonturn Device Type:**

Pin at 3:00 o'clock

**Operating Temperature Range:**

-65.0/+125.0 degrees celsius

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

2 single section rear

**Throw Quantity:**

2 single section rear

**Mounting Method:**

Threaded bushing single mounting facility

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Shaft Flat/slot Angular Location:**

270.0 degrees from nonturn device single actuator

**Switch Actuator Indexing Position Quantity:**

2 single actuator

**Shaft Type:**

Round, flatted single actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Breaks before makes single section rear

**Switch Actuator Positioning Increment:**

90.0 degrees single actuator

**Detent Rotational Torque Range:**

+12.000/+64.000 inch-ounces single actuator

**Switch Actuator Stop Device Type:**

Fixed-adjustable stops single actuator

**Contact Load Current Rating:**

200.0 milliamperes resistive load dc at sea level and 20.0 milliamperes inductive load dc at sea level

**Style Designator:**

Circular wafer, bushing mount

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0