NSN 5930-01-018-9186

Rotary Switch - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5930-01-018-9186

Thread Class:

2a single mounting facility

Thread Length:

0.375 inches single mounting facility

Overall Length:

2.047 inches

First Flat Length:

0.250 inches single actuator

Flat Height:

0.221 inches single actuator

Shaft Diameter:

0.270 inches single actuator

Shaft Length:

2.047 inches single actuator

Overall Diameter:

1.120 inches

Individual Section Quantity:

2

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

2 each section front

Throw Quantity:

6 each section rear

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Rotor Through Connection Quantity:

2 each section

Switch Actuator Indexing Position Quantity:

6 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed-adjustable stops single actuator

NSN 5930-01-018-9186

Rotary Switch - Page 2 of 2



Contact	l oad	Current	Rating:
CUIIIACI	∟∪au	Guileiii	naumu.

555.0 milliamperes resistive load dc at sea level

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0