NSN 5930-01-019-1896

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-019-1896

Body Style:
Panel mounted
Hazardous Locations/environmental Protection:
Explosion proof and humidity resistant
Overall Length:
3.635 inches
Overall Height:
0.750 inches
Overall Width:
0.750 inches
Body Width:
0.750 inches
Body Height:
0.750 inches
Case Material:
Metal
Actuator Length:
0.625 inches
Actuator Style:
Rectangular
Actuator Height:
0.100 inches
Actuator Width:
0.625 inches
Actuator Color:
Black single actuator
Illuminated Actuator Color:
Amber single actuator and white single actuator
Actuator Inscription:
Open single actuator
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Mounting Surface To Terminal End Distance:
3.535 inches
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Features Provided:
Full display lens
Nonpile-up Contact Arrangement:

3 pole, double throw, one position momentary single switch unit

NSN 5930-01-019-1896

Push Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive ac and 3.500 amperes inductive ac and 1.000 amperes lamp ac and 7.500 amperes resistive dc and 5.000 amperes inductive dc and 1.000 amperes lamp dc

Special Features:

Inscription on actuator is printed from top to bottom

Precious Material And Location:

Contacts silver

Terminal Type And Quantity:

1 socket, integrated wire termination

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0