NSN 5930-01-019-3743

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-019-3743

Internal deactuation point screw and internal actuation point screw

Hannadava Landina da vida sana atal Basta di an
Hazardous Locations/environmental Protection:
Dustproof
Overall Length:
2.625 inches
Overall Height:
5.250 inches
Overall Width:
3.500 inches
Body Height:
4.625 inches
Unthreaded Mounting Hole Diameter:
0.219 inches
Distance Between Mounting Facility Centers:
2.000 inches
Capillary Tube Length:
68.5 inches
Bulb Length:
3.750 inches
Bulb Diameter:
0.375 inches
Tempurature Sensing Element Type:
Capillary tube-bulb
Mounting Method:
Unthreaded hole
Features Provided:
Electrical access port
Contact Action Stimulus:
Increase
Mounting Facility Pattern:
Two position in-line
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary
Terminal Type:
Screw
Contact Load Current Rating:
5.0 amperes resistive load second voltage
Contact Adjustability:
Deactuation point adjustable and actuation point adjustable
Contact Adjustment Range:
+140.00/+290.00 actuation point degrees fahrenheit and +147.00/+282.00 deactuation point degrees fahrenheit
Contact Adjustment Type:

NSN 5930-01-019-3743 Thermostatic Switch - Page 2 of 2



Contact Voltage Rating In Volt
600.0 ac at sea level first voltage
Media For Which Designed:
Gas or liquid
Style Designator:
Rectangular
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No Fiig: A048b0