

View Online at <https://aerobasegroup.com/nsn/5930-01-019-3743>

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

2.625 inches

Overall Height:

5.250 inches

Overall Width:

3.500 inches

Body Height:

4.625 inches

Unthreaded Mounting Hole Diameter:

0.219 inches

Distance Between Mounting Facility Centers:

2.000 inches

Capillary Tube Length:

68.5 inches

Bulb Length:

3.750 inches

Bulb Diameter:

0.375 inches

Temperature Sensing Element Type:

Capillary tube-bulb

Mounting Method:

Unthreaded hole

Features Provided:

Electrical access port

Contact Action Stimulus:

Increase

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Screw

Contact Load Current Rating:

5.0 amperes resistive load second voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

+140.00/+290.00 actuation point degrees fahrenheit and +147.00/+282.00 deactuation point degrees fahrenheit

Contact Adjustment Type:

Internal deactuation point screw and internal actuation point screw

Contact Voltage Rating In Volts:

600.0 ac at sea level first voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

FiiG:

A048b0