

View Online at <https://aerobasegroup.com/nsn/5930-01-019-3743>

**Hazardous Locations/environmental Protection:**

Dustproof

**Overall Length:**

2.625 inches

**Overall Height:**

5.250 inches

**Overall Width:**

3.500 inches

**Body Height:**

4.625 inches

**Unthreaded Mounting Hole Diameter:**

0.219 inches

**Distance Between Mounting Facility Centers:**

2.000 inches

**Capillary Tube Length:**

68.5 inches

**Bulb Length:**

3.750 inches

**Bulb Diameter:**

0.375 inches

**Temperature Sensing Element Type:**

Capillary tube-bulb

**Mounting Method:**

Unthreaded hole

**Features Provided:**

Electrical access port

**Contact Action Stimulus:**

Increase

**Mounting Facility Pattern:**

Two position in-line

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary

**Terminal Type:**

Screw

**Contact Load Current Rating:**

5.0 amperes resistive load second voltage

**Contact Adjustability:**

Deactuation point adjustable and actuation point adjustable

**Contact Adjustment Range:**

+140.00/+290.00 actuation point degrees fahrenheit and +147.00/+282.00 deactuation point degrees fahrenheit

**Contact Adjustment Type:**

Internal deactuation point screw and internal actuation point screw

**Contact Voltage Rating In Volts:**

600.0 ac at sea level first voltage

**Media For Which Designed:**

Gas or liquid

**Style Designator:**

Rectangular

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**FiiG:**

A048b0