## NSN 5930-01-019-3746

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-019-3746

Overall Length:
4.875 inches
Overall Height:
2.500 inches
Overall Width:
2.875 inches
Body Length:
4.625 inches
Capillary Tube Length:
120.0 inches
Bulb Length:
3.625 inches
Bulb Diameter:
0.688 inches
Longest Horizontal Distance Between Mounting Centers:
2.406 inches
Shortest Horizontal Distance Between Mounting Centers:
1.750 inches
Longest Vertical Distance Between Mounting Centers:
3.281 inches
Tempurature Sensing Element Type:
Capillary tube-bulb
Operating Tempurature Rating:
167.0 degrees fahrenheit
Mounting Method:
Base
Features Provided:
Electrical access port
Contact Action Stimulus:
Increase
Mounting Facility Pattern:
Isosceles triangle
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary
Terminal Type:
Tab w/screw
Contact Load Current Rating:

**Contact Adjustability:** 

Deactuation point adjustable and actuation point adjustable

**Contact Adjustment Range:** 

3.2 amperes resistive load first voltage

+70.00/+140.00 actuation point degrees fahrenheit and +66.00/+136.00 deactuation point degrees fahrenheit

## NSN 5930-01-019-3746

Thermostatic Switch - Page 2 of 2

No Fiig: A048b0



## Contact Adjustment Type: External deactuation point screw and external actuation point screw Contact Voltage Rating In Volts: 550.0 ac at sea level first voltage Media For Which Designed: Gas or liquid Style Designator: Rectangular Shelf Life: N/a Unit Of Measure: - Demilitarization: