NSN 5930-01-019-5216

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-019-5216 **Overall Length:** 5.406 inches **Overall Height:** 5.000 inches Overall Width: 2.812 inches **Body Length:** 2.750 inches **Capillary Tube Length:** 120.0 inches **Longest Horizontal Distance Between Mounting Centers:** 2.406 inches **Shortest Horizontal Distance Between Mounting Centers:** 1.203 inches **Longest Vertical Distance Between Mounting Centers:** 3.281 inches **Tempurature Sensing Element Type:** Capillary tube **Operating Tempurature Rating:** 500.0 degrees fahrenheit **Mounting Method: Bracket Contact Action Stimulus:** Increase **Mounting Facility Pattern:** Isosceles triangle **Nonpile-up Contact Arrangement:** 1 two circuit, double break/double make, one position momentary

Terminal Type:

Screw

Contact Load Current Rating:

3.4 amperes resistive load first voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

+375.00/+480.00 actuation point degrees fahrenheit and +373.00/+475.00 deactuation point degrees fahrenheit

Contact Adjustment Type:

External deactuation point screw and external actuation point screw

Contact Voltage Rating In Volts:

550.0 ac at sea level first voltage

Frequency In Hertz:

60.0 first voltage

NSN 5930-01-019-5216

Thermostatic Switch - Page 2 of 2



Media For Which Designed:
Gas or liquid
Style Designator:
Rectangular
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A048b0