

View Online at <https://aerobasegroup.com/nsn/5930-01-019-5261>

**Body Style:**

Bushing mount

**Hazardous Locations/environmental Protection:**

Dustproof

**Bushing Length:**

0.470 inches

**Body Length:**

1.320 inches

**Body Width:**

0.890 inches

**Body Height:**

1.100 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.420 inches

**Actuator Height:**

1.050 inches

**Actuator Position-action Relationship:**

Up position maintained and down position momentary and center position maintained

**Actuator Position-locking Relationship:**

Up position locked in and down position no locking action and center position no locking action

**Maximum Voltage Rating In Volts:**

250.0 ac and 250.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Features Provided:**

Actuator seal

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.469 inches

**Nonpile-up Contact Arrangement:**

2 pole, double throw, one position momentary, two positions maintained single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

500.000 milliamperes resistive dc and 6.000 amperes resistive ac

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

6 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0