NSN 5930-01-019-5261

Toggle Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-019-5261

| Body Style: | | | | |
|---|--|--|--|--|
| Bushing mount | | | | |
| Hazardous Locations/environmental Protection: | | | | |
| Dustproof | | | | |
| Bushing Length: | | | | |
| 0.470 inches | | | | |
| Body Length: | | | | |
| 1.320 inches | | | | |
| Body Width: | | | | |
| 0.890 inches | | | | |
| Body Height: | | | | |
| 1.100 inches | | | | |
| Actuator Style: | | | | |
| Round | | | | |
| Actuator Diameter: | | | | |
| 0.420 inches | | | | |
| Actuator Height: | | | | |
| 1.050 inches | | | | |
| Actuator Position-action Relationship: | | | | |
| Up position maintained and down position momentary and center position maintained | | | | |
| Actuator Position-locking Relationship: | | | | |
| Up position locked in and down position no locking action and center position no locking action | | | | |
| Maximum Voltage Rating In Volts: | | | | |
| 250.0 ac and 250.0 dc | | | | |
| Inclosure Type: | | | | |
| Fully enclosed | | | | |
| Mounting Method: | | | | |
| Threaded bushing | | | | |
| Features Provided: | | | | |
| Actuator seal | | | | |
| Thready Qty Per Inch (tpi): | | | | |
| 32 | | | | |
| Thread Size: | | | | |
| 0.469 inches | | | | |
| Nonpile-up Contact Arrangement: | | | | |
| 2 pole, double throw, one position momentary, two positions maintained single switch unit | | | | |
| Contact Load Current Rating At Maximum Rated Voltage: | | | | |
| 500.000 milliamperes resistive dc and 6.000 amperes resistive ac | | | | |
| Thread Series Designator: | | | | |
| Uns | | | | |
| Terminal Type And Quantity: | | | | |

6 screw

NSN 5930-01-019-5261

Toggle Switch - Page 2 of 2



| _ | | | | |
|---|----|------|---|------|
| c | hο | JIF. | | ife: |
| J | | | _ | HG. |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0