NSN 5930-01-019-5270

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-019-5270

Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Dustproof
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.000 inches
Body Length:
1.940 inches
Body Width:
0.687 inches
Body Height:
1.150 inches
Unthreaded Mounting Hole Diameter:
0.139 inches
Actuator Length:
1.026 inches
Actuator Style:
Roller arm
Actuator Free Position Height:
1.281 inches
Actuator Roller Diameter:
0.370 inches
Actuator Roller Width:
0.150 inches
Maximum Voltage Rating In Volts:
480.0 ac and 250.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Nonpile-up Contact Arrangement:
1 pole, double throw, two positions momentary single switch unit
Switch Release Force:
1.5 ounces
Switch Actuating Force:
6.0 ounces
Actuator Movement:
Between 0.094 overtravel inches and 0.003 differential inches
Contact Load Current Rating At Maximum Rated Voltage:

250.000 milliamperes resistive dc and 15.000 amperes resistive ac **Terminal Type And Quantity:**

3 screw

NSN 5930-01-019-5270

Sensitive Switch - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0