

View Online at <https://aerobasegroup.com/nsn/5930-01-019-5274>

**Body Style:**

Hole mounted

**Hazardous Locations/environmental Protection:**

Weatherproof

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

Between 0.204 inches and 0.224 inches

**Body Length:**

Between 0.606 inches and 0.626 inches

**Body Width:**

Between 0.306 inches and 0.326 inches

**Body Height:**

Between 0.570 inches and 0.630 inches

**Case Material:**

Metal

**Unthreaded Mounting Hole Diameter:**

0.091 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.060 inches

**Actuator Free Position Height:**

0.495 inches

**Maximum Voltage Rating In Volts:**

28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Unthreaded hole

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

2.0 ounces

**Switch Actuating Force:**

10.0 ounces

**Actuator Movement:**

Between 0.004 pretravel inches and 0.004 overtravel inches and 0.005 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

7.000 amperes resistive dc and 4.000 amperes inductive dc

**Terminal Type And Quantity:**

3 wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0