

View Online at <https://aerobasegroup.com/nsn/5930-01-019-5274>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Weatherproof

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 0.204 inches and 0.224 inches

Body Length:

Between 0.606 inches and 0.626 inches

Body Width:

Between 0.306 inches and 0.326 inches

Body Height:

Between 0.570 inches and 0.630 inches

Case Material:

Metal

Unthreaded Mounting Hole Diameter:

0.091 inches

Actuator Style:

Round

Actuator Diameter:

0.060 inches

Actuator Free Position Height:

0.495 inches

Maximum Voltage Rating In Volts:

28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

2.0 ounces

Switch Actuating Force:

10.0 ounces

Actuator Movement:

Between 0.004 pretravel inches and 0.004 overtravel inches and 0.005 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive dc and 4.000 amperes inductive dc

Terminal Type And Quantity:

3 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0