

View Online at <https://aerobasegroup.com/nsn/5930-01-019-6891>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Oiltight

Switch Actuator Quantity:

1

Actuator Style:

Roller plunger

Actuator Roller Diameter:

0.500 inches

Housing Height:

1.785 inches

Housing Length:

4.685 inches

Housing Width:

1.875 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Height:

1.156 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Length:

2.344 inches

Maximum Voltage Rating In Volts:

600.0 ac and 240.0 dc

Inclosure Type:

Fully enclosed

Features Provided:

Actuator seal

Nonpile-up Contact Arrangement:

2 two circuit, double break/double make, one position momentary single switch unit

Switch Actuating Force:

96.0 ounces

Actuator Movement:

Between 0.100 pretravel inches and 0.190 overtravel inches and 0.035 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

400.000 milliamperes resistive dc and 150.000 milliamperes inductive dc and 600.000 milliamperes inductive ac

Terminal Type And Quantity:

8 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0