

View Online at <https://aerobasegroup.com/nsn/5930-01-019-6891>

**Body Style:**

Hole mounted

**Hazardous Locations/environmental Protection:**

Oiltight

**Switch Actuator Quantity:**

1

**Actuator Style:**

Roller plunger

**Actuator Roller Diameter:**

0.500 inches

**Housing Height:**

1.785 inches

**Housing Length:**

4.685 inches

**Housing Width:**

1.875 inches

**Center To Center Distance Between Housing Mounting Facilities Parallel To Height:**

1.156 inches

**Center To Center Distance Between Housing Mounting Facilities Parallel To Length:**

2.344 inches

**Maximum Voltage Rating In Volts:**

600.0 ac and 240.0 dc

**Inclosure Type:**

Fully enclosed

**Features Provided:**

Actuator seal

**Nonpile-up Contact Arrangement:**

2 two circuit, double break/double make, one position momentary single switch unit

**Switch Actuating Force:**

96.0 ounces

**Actuator Movement:**

Between 0.100 pretravel inches and 0.190 overtravel inches and 0.035 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

400.000 milliamperes resistive dc and 150.000 milliamperes inductive dc and 600.000 milliamperes inductive ac

**Terminal Type And Quantity:**

8 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0