NSN 5930-01-019-9765

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-019-9765

Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Corrosion resistant
Center To Center Distance Between Mounting Facilities Parallel To Length:
0.875 inches
Body Length:
1.094 inches
Body Width:
0.400 inches
Body Height:
0.625 inches
Unthreaded Mounting Hole Diameter:
Between 0.114 inches and 0.126 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
0.406 inches
Switch Actuator Quantity:
1
Actuator Length:
0.110 inches
Actuator Style:
Rectangular
Actuator Height:
0.062 inches
Actuator Width:
0.165 inches
Actuator Free Position Height:
0.109 inches
Maximum Voltage Rating In Volts:
250.0 ac and 250.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Switch Release Force:
4.0 ounces
Switch Actuating Force:
14.0 ounces
Actuator Movement:
0.047 pretravel inches and 0.040 overtravel inches and 0.016 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

250.000 milliamperes resistive dc and 15.000 amperes resistive ac

NSN 5930-01-019-9765

Sensitive Switch - Page 2 of 2



Terminal Type A	nd Quantity:
-----------------	--------------

2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0