

View Online at <https://aerobasegroup.com/nsn/5930-01-019-9765>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Corrosion resistant

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.875 inches

Body Length:

1.094 inches

Body Width:

0.400 inches

Body Height:

0.625 inches

Unthreaded Mounting Hole Diameter:

Between 0.114 inches and 0.126 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.406 inches

Switch Actuator Quantity:

1

Actuator Length:

0.110 inches

Actuator Style:

Rectangular

Actuator Height:

0.062 inches

Actuator Width:

0.165 inches

Actuator Free Position Height:

0.109 inches

Maximum Voltage Rating In Volts:

250.0 ac and 250.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Switch Release Force:

4.0 ounces

Switch Actuating Force:

14.0 ounces

Actuator Movement:

0.047 pretravel inches and 0.040 overtravel inches and 0.016 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

250.000 milliamperes resistive dc and 15.000 amperes resistive ac

Terminal Type And Quantity:

2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0