

View Online at <https://aerobasegroup.com/nsn/5930-01-020-1698>

Body Style:

Bushing mount

Overall Length:

0.688 inches

Overall Height:

1.938 inches

Overall Width:

0.672 inches

Bushing Length:

Between 0.458 inches and 0.478 inches

Body Length:

0.688 inches

Body Width:

0.672 inches

Actuator Style:

Round

Actuator Diameter:

Between 0.237 inches and 0.246 inches

Actuator Height:

Between 0.655 inches and 0.719 inches

Actuator Position-action Relationship:

Up position maintained and down position maintained and center position maintained

Maximum Voltage Rating In Volts:

115.0 ac and 50.0 dc

Mounting Surface To Terminal End Distance:

0.741 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Features Provided:

Actuator seal

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, three positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

1.000 amperes resistive dc and 3.000 amperes resistive ac and 3.000 amperes inductive ac

Thread Series Designator:

Uns

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0