

View Online at <https://aerobasegroup.com/nsn/5930-01-020-2517>

Thread Class:

2a single mounting facility

Thread Length:

0.245 inches single mounting facility and 0.255 inches single mounting facility

Hazardous Locations/environmental Protection:

Explosion proof

Overall Length:

Between 1.094 inches and 1.156 inches

Shaft Diameter:

0.123 inches single actuator and 0.127 inches single actuator

Shaft Length:

0.780 inches single actuator and 0.840 inches single actuator

Overall Diameter:

Between 0.495 inches and 0.512 inches

Individual Section Quantity:

1

Nonturn Device Type:

Flatted bushing at 3: 00 o'clock flatted bushing at 9: 00 o'clock

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

3 single section rear

Throw Quantity:

2 single section rear

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.250 inches single mounting facility

Contact Voltage Rating In Volts:

115.0 ac at sea level 28.0 highest dc voltage rating at sea level 6.0 lowest dc voltage rating at sea level

Switch Actuator Indexing Position Quantity:

2 single actuator

Shaft Type:

Round single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes single section rear

Switch Actuator Positioning Increment:

60.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

250.0 milliamperes resistive load ac at sea level1.0 amperes resistive load highest dc voltage rating at sea level1.0 amperes resistive load lowest dc voltage rating at sea level

Precious Material And Location:

Contacts and totor blades silver and contact and rotor blade surfaces gold

Precious Material:

Silver and gold

Style Designator:

Miniature, bushing mount

Thread Series Designator:

Unf single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0