

View Online at <https://aerobasegroup.com/nsn/5930-01-020-3307>

Thread Class:

2b single pressure connection

Inside Diameter:

0.438 inches single connection

Overall Length:

4.875 inches

Overall Height:

4.500 inches

Overall Width:

2.625 inches

Body Length:

4.625 inches

Body Height:

2.500 inches

Longest Horizontal Distance Between Mounting Centers:

2.406 inches

Shortest Horizontal Distance Between Mounting Centers:

1.750 inches

Longest Vertical Distance Between Mounting Centers:

3.281 inches

Pressure Switch Type:

Gage

Temperature Sensing Element Type:

Internal sensor

Mounting Method:

Bracket

Features Provided:

Electrical access port

Contact Action Stimulus:

Decrease

Proof Pressure:

160.00 pounds per square inch gage

Thread Size:

0.438 inches single pressure connection

Mounting Facility Pattern:

Isosceles triangle

Nonpile-up Contact Arrangement:

1 pole, single throw, normally closed, momentary action

Terminal Type:

Tab w/screw

Contact Load Current Rating:

3.2 amperes resistive load second voltage

Contact Adjustability:

Deactuation point adjustable, preset and actuation point adjustable, preset

Contact Adjustment Range:

+15.00/+50.00 actuation point pounds per square inch gage and +9.00/+44.00 deactuation point pounds per square inch gage

Contact Adjustment Type:

External deactuation point screw and external actuation point screw

Contact Stimulus Rating:

32.00 actuation point pounds per square inch gage and 26.00 deactuation point pounds per square inch gage

Contact Voltage Rating In Volts:

550.0 ac at sea level second voltage

Pressure Connector Type:

Inverted flare, threaded internal single connection

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular w/mounting lugs

Thread Series Designator:

Unf single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0