

View Online at <https://aerobasegroup.com/nsn/5930-01-020-9597>

Thread Class:

2b single pressure connection

Overall Length:

10.938 inches

Overall Height:

3.000 inches

Overall Width:

5.750 inches

Longest Horizontal Distance Between Mounting Centers:

3.000 inches

Shortest Horizontal Distance Between Mounting Centers:

1.500 inches

Longest Vertical Distance Between Mounting Centers:

4.250 inches

Pressure Switch Type:

Gage

Mounting Method:

Bracket

Features Provided:

Electrical access port

Thready Qty Per Inch (tpi):

20 single pressure connection

Contact Action Stimulus:

Increase

Proof Pressure:

3600.00 pounds per square inch gage

Thread Size:

0.438 inches single pressure connection

Mounting Facility Pattern:

Isosceles triangle

Nonpile-up Contact Arrangement:

1 pole, single throw, normally closed, momentary action

Terminal Type:

Tab w/screw

Contact Load Current Rating:

3.2 amperes resistive load first voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

+250.00/+3000.00 actuation point pounds per square inch gage and +210.00/+2910.00 deactuation point pounds per square inch gage

Contact Adjustment Type:

External deactuation point screw and external actuation point screw

Contact Voltage Rating In Volts:

550.0 ac at sea level first voltage

Pressure Connector Type:

Gasket seal, threaded internal single connection

Media For Which Designed:

Gas

Style Designator:

Rectangular w/bracket

Thread Series Designator:

Unef single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0