

View Online at <https://aerobasegroup.com/nsn/5930-01-020-9632>

**Body Style:**

Bushing mount

**Overall Length:**

0.572 inches

**Overall Height:**

1.359 inches

**Overall Width:**

0.556 inches

**Bushing Length:**

Between 0.160 inches and 0.180 inches

**Body Length:**

0.572 inches

**Body Width:**

0.556 inches

**Case Material:**

Metal

**Actuator Style:**

Round

**Actuator Diameter:**

Between 0.090 inches and 0.096 inches

**Actuator Height:**

Between 0.415 inches and 0.465 inches

**Actuator Position-action Relationship:**

Up position maintained and down position momentary and center position maintained

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**End Application:**

Ticonderoga class cg (47); sonar, signal processing sys, an/sqq-2 (v); nimitz class cvn; aircraft, (ac-130h, mc-130h, ec-130e, hc-130) ; sturgeon

**Mounting Surface To Terminal End Distance:**

0.749 inches

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Features Provided:**

Actuator seal

**Thready Qty Per Inch (tpi):**

40

**Thread Size:**

0.250 inches

**Nonpile-up Contact Arrangement:**

2 pole, double throw, one position momentary, two positions maintained single switch unit

**Criticality Code Justification:**

Feat

**Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive dc and 1.000 amperes resistive dc and 2.000 amperes resistive ac and 1.000 amperes inductive ac

**Special Features:**

Weapon system essential

**Test Data Document:**

81349-mil-s-8834 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

6 tab, solder lug

**Specification Data:**

96906-ms24656 government standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0