

View Online at <https://aerobasegroup.com/nsn/5930-01-020-9807>

Overall Length:

7.250 inches

Overall Height:

2.250 inches

Body Diameter:

5.750 inches

Pressure Switch Type:

Differential

Width Across Flats:

0.5625 inches

Mounting Method:

Flange and threaded hole

Thready Qty Per Inch (tpi):

18 single pressure connection

Contact Action Stimulus:

Increase

Thread Size:

0.250 inches single pressure connection

Mounting Facility Pattern:

Isosceles triangle

Contact Load Current Rating:

5.0 amperes resistive load third voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

+25.00/+600.00 actuation point pounds per square inch gage and +25.00/+600.00 deactuation point pounds per square inch gage

Contact Adjustment Type:

External deactuation point knob and external actuation point knob

Contact Stimulus Rating:

25.00 differential point pounds per square inch gage

Contact Voltage Rating In Volts:

440.0 ac at sea level first voltage

Pressure Connector Type:

External seat-gasket seal, threaded external single connection

Media For Which Designed:

Gas or liquid

Style Designator:

Cylindrical w/port

Thread Series Designator:

Npt single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0