

View Online at <https://aerobasegroup.com/nsn/5930-01-021-2344>

**Body Style:**

Hole mounted

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

0.375 inches

**Body Length:**

0.781 inches

**Body Width:**

0.250 inches

**Body Height:**

0.359 inches

**Unthreaded Mounting Hole Diameter:**

0.088 inches

**Actuator Style:**

Roller arm

**Actuator Free Position Height:**

0.570 inches

**Actuator Roller Diameter:**

0.188 inches

**Actuator Roller Width:**

0.109 inches

**Maximum Voltage Rating In Volts:**

250.0 ac and 30.0 dc

**End Application:**

Sturgeon class ssn (637), trident hull structure, nimitz class cvn, emory s. Land class as, los angeles class ssn (688), galley equipment & food service, submarine auxiliary and miscellaneous systems, radiation detection indication & computation (radiac) eqpt, yellowstone class ad-41.

**Inclosure Type:**

Fully enclosed

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

0.5 ounces

**Criticality Code Justification:**

Feat

**Switch Actuating Force:**

6.0 ounces

**Actuator Movement:**

0.094 pretravel inches and 0.047 overtravel inches and 0.031 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

3.000 amperes inductive dc and 5.000 amperes resistive dc and 5.000 amperes inductive ac and 5.000 amperes resistive ac

**Special Features:**

Weapon system essential

**Terminal Type And Quantity:**

3 turret

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0