

View Online at <https://aerobasegroup.com/nsn/5930-01-021-5294>

Thread Class:

2a

Body Style:

Bushing mount

Bushing Length:

Between 0.342 inches and 0.362 inches

Body Length:

Between 0.440 inches and 0.460 inches

Body Width:

Between 0.495 inches and 0.505 inches

Body Height:

0.410 inches

Case Material:

Plastic

Switch Actuator Quantity:

1

Actuator Style:

Round

Actuator Diameter:

Between 0.114 inches and 0.116 inches

Actuator Height:

Between 0.390 inches and 0.410 inches

Actuator Position-action Relationship:

Up position maintained and down position maintained and center position maintained

Maximum Voltage Rating In Volts:

125.0 ac and 24.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

40

Thread Size:

0.250 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, three positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 5.000 amperes resistive ac

Thread Series Designator:

Uns

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0