

View Online at <https://aerobasegroup.com/nsn/5930-01-021-5591>

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Explosion proof

Body Diameter:

0.530 inches

Bushing Length:

0.470 inches

Body Length:

0.400 inches

Case Material:

Metal

Actuator Style:

Round

Actuator Diameter:

0.240 inches

Actuator Height:

0.450 inches

Actuator Position-action Relationship:

Up position maintained and down position maintained

Maximum Voltage Rating In Volts:

125.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

6.000 amperes resistive dc and 2.000 amperes inductive dc and 6.000 amperes resistive ac and 2.000 amperes inductive ac

Special Features:

Nickel plated brass slotted keyway bushing

Thread Series Designator:

Uns

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0