

View Online at <https://aerobasegroup.com/nsn/5930-01-022-2049>

Thread Class:

3a single pressure connection

Inside Diameter:

0.438 inches single connection

Overall Length:

3.334 inches

Overall Height:

1.625 inches

Overall Width:

1.750 inches

Body Length:

2.260 inches

Unthreaded Mounting Hole Diameter:

0.203 inches

Distance Between Mounting Facility Centers:

2.250 inches

Pressure Switch Type:

Gage

Operating Temperature Rating:

Between -65.0 degrees fahrenheit and 275.0 degrees fahrenheit

Mounting Method:

Bracket and unthreaded hole

Contact Action Stimulus:

Decrease

Proof Pressure:

1000.00 pounds per square inch gage

Thread Size:

0.438 inches single pressure connection

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action

Sensing Element Burst Pressure:

2500.00 pounds per square inch gage

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

5.0 amperes resistive load single voltage and 2.5 amperes inductive load single voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point adjustable, preset

Contact Adjustment Range:

+2.00/+10.00 actuation point pounds per square inch

Contact Adjustment Type:

External actuation point pointer

Contact Stimulus Rating:

5.00 actuation point pounds per square inch and 4.00 deactuation point pounds per square inch

Contact Voltage Rating In Volts:

30.0 dc at sea level single voltage

Pressure Connector Type:

Plain, threaded internal single connection

Media For Which Designed:

Gas or liquid

Style Designator:

Cylindrical

Thread Series Designator:

Unf single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0