NSN 5930-01-022-2065

Rotary Switch - Page 1 of 2

Thread Class:



View Online at https://aerobasegroup.com/nsn/5930-01-022-2065

2a single mounting facility Thread Length: 0.250 inches single mounting facility **Hazardous Locations/environmental Protection:** Dustproof **Overall Length:** 1.275 inches **Shaft Diameter:** 0.125 inches single actuator **Shaft Length:** 0.625 inches single actuator **Overall Diameter:** 0.500 inches **Individual Section Quantity: Nonturn Device Type:** Flatted bushing at 3: 00 o'clock **Switch Contact Basic Design:** Nonpile-up symmetrical **Pole Quantity:** 1 single section rear **Throw Quantity:** 6 single section rear **Mounting Method:** Threaded bushing single mounting facility **Thread Size:** 0.250 inches single mounting facility **Contact Voltage Rating In Volts:** 115.0 ac at sea level **Switch Actuator Indexing Position Quantity:** 6 single actuator **Shaft Type:** Round single actuator **Terminal Type:** Tab, solder lug **Contact Switching Action:** Breaks before makes single section rear **Switch Actuator Positioning Increment:** 36.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

NSN 5930-01-022-2065

Rotary Switch - Page 2 of 2



Contact Load	Current	Rating:
--------------	---------	---------

50.0 milliamperes resistive load ac at sea level

Style Designator:

Snap or line

Thread Series Designator:

Unf single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0