

View Online at <https://aerobasegroup.com/nsn/5930-01-022-2809>

**Body Style:**

Bushing mount

**Hazardous Locations/environmental Protection:**

Explosion proof

**Body Diameter:**

1.000 inches

**Bushing Length:**

0.470 inches

**Body Length:**

1.870 inches

**Switch Actuator Quantity:**

1

**Actuator Style:**

Rectangular

**Actuator Height:**

0.690 inches

**Actuator Width:**

0.375 inches

**Actuator Color:**

Gray single actuator

**Maximum Voltage Rating In Volts:**

28.0 dc

**Inclosure Type:**

Fully enclosed

**Features Provided:**

Actuator seal

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.469 inches

**Nonpile-up Contact Arrangement:**

2 pole, double throw, one position momentary single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

4.000 amperes resistive dc and 2.500 amperes inductive dc and 4.000 amperes motor dc

**Special Features:**

Solenoid holding coil 460 ohms min dc resistance, hold in 15 to 29 volts dc drop out 15 to 0 volts dc at 20 degrees celsius

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

8 turret

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0