

View Online at <https://aerobasegroup.com/nsn/5930-01-022-6570>

**Thread Length:**

0.292 inches single mounting facility and 0.332 inches single mounting facility

**Hazardous Locations/environmental Protection:**

Explosion proof

**Overall Length:**

3.908 inches

**Overall Width:**

Between 0.986 inches and 1.006 inches

**First Flat Length:**

0.230 inches single actuator and 0.270 inches single actuator

**Flat Height:**

0.215 inches single actuator and 0.223 inches single actuator

**Shaft Diameter:**

0.248 inches single actuator and 0.251 inches single actuator

**Shaft Length:**

0.647 inches single actuator and 0.727 inches single actuator

**Individual Section Quantity:**

11

**Nonturn Device Type:**

Slotted bushing at 3: 00 o'clock

**Operating Temperature Range:**

-65.0/+125.0 degrees celsius

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 each section front

**Throw Quantity:**

5 each section rear

**Mounting Method:**

Threaded bushing single mounting facility

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

30.0 dc at sea level

**Shaft Flat/slot Angular Location:**

105.0 degrees from nonturn device single actuator

**Rotor Through Connection Quantity:**

1 each section

**Switch Actuator Indexing Position Quantity:**

10 single actuator

**Shaft Type:**

Round, flatted single actuator

**Terminal Type:**

Printed circuit

**Contact Switching Action:**

Breaks before makes each section rear

**Switch Actuator Positioning Increment:**

36.0 degrees single actuator

**Detent Rotational Torque Range:**

+4.000/+32.000 inch-ounces single actuator

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Contact Load Current Rating:**

500.0 milliamperes resistive load dc at sea level and 250.0 milliamperes inductive load dc at sea level

**Style Designator:**

Wafer, printed board, bushing mount

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0