

View Online at <https://aerobasegroup.com/nsn/5930-01-023-1455>

Thread Length:

0.370 inches single mounting facility and 0.380 inches single mounting facility

Overall Length:

3.005 inches

Overall Height:

Between 1.516 inches and 1.546 inches

Overall Width:

Between 1.297 inches and 1.327 inches

First Flat Length:

0.360 inches single actuator and 0.390 inches single actuator

Flat Height:

0.212 inches single actuator and 0.220 inches single actuator

Shaft Diameter:

0.245 inches single actuator and 0.250 inches single actuator

Shaft Length:

0.860 inches single actuator and 0.900 inches single actuator

Nonturn Device Radius:

0.521 inches at 3: 00 o'clock and 0.541 inches at 3: 00 o'clock

Individual Section Quantity:

3

Nonturn Device Type:

Tab at 3: 00 o'clock

Operating Temperature Range:

-65.0/+85.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section rear

Throw Quantity:

3 each section rear

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Shaft Flat/slot Angular Location:

105.0 degrees from nonturn device single actuator

Switch Actuator Indexing Position Quantity:

3 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Makes before breaks 1st section rear

Switch Actuator Positioning Increment:

60.0 degrees single actuator

Contact Load Current Rating:

1.0 amperes resistive load ac at sea level

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0