

View Online at <https://aerobasegroup.com/nsn/5930-01-023-2566>

**Thread Class:**

2a

**Body Style:**

Bushing mount

**Hazardous Locations/environmental Protection:**

Explosion proof

**Bushing Length:**

0.315 inches

**Body Length:**

0.701 inches

**Body Width:**

0.512 inches

**Body Height:**

0.530 inches

**Case Material:**

Plastic

**Actuator Style:**

Round

**Actuator Diameter:**

0.217 inches

**Actuator Height:**

Between 0.590 inches and 0.650 inches

**Actuator Position-action Relationship:**

Up position maintained and down position maintained

**Actuator Position-locking Relationship:**

Up position locked in and down position locked in

**Maximum Voltage Rating In Volts:**

250.0 ac

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Thready Qty Per Inch (tpi):**

40

**Thread Size:**

0.250 inches

**Nonpile-up Contact Arrangement:**

3 pole, double throw, both positions maintained single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

3.000 amperes resistive ac

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

9 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0