

View Online at <https://aerobasegroup.com/nsn/5930-01-023-6938>

**Thread Class:**

2a all threaded stud

**Thread Length:**

0.250 inches all threaded stud and 0.320 inches all threaded stud

**Overall Height:**

Between 0.865 inches and 0.924 inches

**Body Height:**

Between 0.361 inches and 0.367 inches

**Overall Diameter:**

Between 0.623 inches and 0.640 inches

**Temperature Sensing Element Type:**

Internal sensor

**Operating Temperature Rating:**

100.0 degrees celsius and -62.0 degrees celsius

**Mounting Method:**

Threaded stud

**Features Provided:**

Hermetically sealed case

**Thready Qty Per Inch (tpi):**

32 all threaded stud

**Contact Action Stimulus:**

Increase

**Thread Size:**

0.138 inches all threaded stud

**Nonpile-up Contact Arrangement:**

1 pole, single throw, normally closed, momentary action

**Terminal Type:**

Tab, solder lug

**Contact Load Current Rating:**

5.0 amperes resistive load third voltage

**Contact Adjustability:**

Deactuation point not adjustable and actuation point not adjustable

**Contact Stimulus Rating:**

288.00 actuation point degrees fahrenheit and 300.00 actuation point degrees fahrenheit and 256.00 deactuation point degrees fahrenheit and 272.00 deactuation point degrees fahrenheit and 30.00 differential point degrees fahrenheit

**Contact Voltage Rating In Volts:**

30.0 ac at sea level third voltage

**Frequency In Hertz:**

60.0 single voltage

**Media For Which Designed:**

Gas or liquid

**Style Designator:**

Disc

**Thread Series Designator:**

Unc all threaded stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0