

View Online at <https://aerobasegroup.com/nsn/5930-01-023-6943>

Thread Class:

2a

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Dustproof

Bushing Length:

0.500 inches

Body Length:

1.300 inches

Body Width:

0.670 inches

Actuator Style:

Round

Actuator Diameter:

0.240 inches

Actuator Height:

0.656 inches

Actuator Position-action Relationship:

Up position momentary and down position momentary

Maximum Voltage Rating In Volts:

250.0 ac and 28.0 dc

Mounting Surface To Terminal End Distance:

1.150 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

4 pole, double throw, two positions momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

24.000 amperes resistive dc and 7.500 amperes inductive dc and 2.500 amperes lamp dc and 4.000 amperes motor dc and 15.000 amperes resistive ac and 7.000 amperes inductive ac

Thread Series Designator:

Uns

Terminal Type And Quantity:

12 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0